

The following ropes are approved for use with the Akimbo at the Working Load Limit (WLL) shown below. Only approved ropes should be used with the Akimbo. For CE compliance, only approved EN1891 Type A ropes are permitted. Edelrid Direction Up and Teufelberger Tachyon were used for CE testing. Working Load is equal to the total weight of the climber including gear.

Total Working Load of the climber must not exceed the Working Load Limit (WLL) for the rope listed below or slippage may occur!



Suitability of approved ropes can be affected by environmental factors, condition of rope, and condition of Akimbo. Follow steps on pages 8-11 to test rope and verify friction settings before climbing.

Check www.rockexotica.com/akimbo for updates to the list of approved ropes.

## TABLE A

WLL: 100kg (220lb) Do Not Exceed this weight on the ropes listed below!			
MANUFACTUR-	MODEL	DIA. (mm)	
Courant	Squir	11.5	
Liros	Safe Plus	11.5	
Marlow	Venom	11.8	
Samson	Voyager Cool	11.8	
Teufelberger	XStatic	11.7	
Yale	Poison Ivy / Blue Moon	11.7	

## TABLE B

## WLL: 130kg (286lb)

Do Not Exceed this weight on the ropes listed below!

MANUFACTUR-	MODEL	DIA. (mm)
All Gear	Cherry Bomb II	11.8
Cousin	Atrax	11.6
Cousin	Lignum	12.5
Drayer	Tango StatX	11.5
Edelrid	Direction Up	13
English Braids	Silvatex 16	12.4
FTC	NIgma	12
FTC	Acid	12.1
Liros	Safe Vision	12.8
Notch	Banshee	11.7
Notch	Sasquatch	13
Samson	ArborMaster	12
Samson	Vortex	12.7
Sterling	Element	12.8
Sterling	Scion	12.5
Sterling	WorkPro	12.5
Sterling	НТР	12.5
Teufelberger	Fly	11.1
Teufelberger	Drenaline	11.8
Teufelberger	Tachyon	11.5
Yale	Scandere	11.7